

PERFORMANCE CURVE FOR CULVERT 1 - One (3300 mm BY 1200 mm) RCB

DIS- CHARGE FLOW (m ³ /s)	HEAD- WATER ELEV. (m)	INLET CONTROL DEPTH (m)	OUTLET CONTROL DEPTH (m)	FLOW TYPE <F4>	NORMAL DEPTH (m)	CRIT. DEPTH (m)	OUTLET DEPTH (m)	TW DEPTH (m)	OUTLET VEL. (m/s)	TW VEL. (m/s)
0.00	57.20	0.00	-0.09	0-NF	0.00	0.00	0.00	0.00	0.00	0.00
0.63	57.51	0.23	0.31	3-Mlt	0.21	0.16	0.35	0.35	0.55	0.47
1.26	57.70	0.37	0.50	3-Mlt	0.34	0.25	0.52	0.52	0.73	0.59
1.89	57.85	0.48	0.65	3-Mlt	0.44	0.32	0.66	0.66	0.87	0.68
2.52	57.99	0.58	0.78	3-Mlt	0.53	0.39	0.77	0.77	0.98	0.74
3.15	58.11	0.68	0.91	3-Mlt	0.62	0.45	0.86	0.86	1.11	0.81
3.78	58.21	0.77	1.01	3-Mlt	0.70	0.51	0.94	0.94	1.22	0.87
4.20	58.25	0.84	1.05	3-Mlt	0.75	0.55	0.99	0.99	1.28	0.90
5.04	58.37	0.95	1.16	3-Mlt	0.85	0.62	1.08	1.08	1.41	0.96
5.67	58.41	1.04	1.22	3-Mlt	0.92	0.67	1.09	1.09	1.58	0.97
6.30	58.46	1.12	1.26	3-Mlt	0.99	0.72	1.09	1.09	1.75	0.97

El. inlet face invert	57.20 m	El. outlet invert	57.11 m
El. inlet throat invert	0.00 m	El. inlet crest	0.00 m

PRESS: <KEY> TO CONTINUE <W> FOR PROFILE TABLE
 <P> TO PLOT <I> FOR IMPROVED INLET TABLE

1- Help 2 3 4-Type 5-End 6 7 8 9-DOS 10

**HY8 PERFORMANCE CURVE PROMPT SCREEN
 3300 mm SPAN BY 1200 mm RISE CULVERT**

Figure 31-8H